# Illumination units for KITOZOOM

## LED-R



The scope of delivery of the systems described on the previous four pages includes the LED-R ring light. For many applications LED ring lights suffice for the top lighting. The LED-R with its 98 white LEDs, arranged at an angle of 15° in three rows, offers perfect illumination quality. The outer diameter is 67 mm and the opening inside 35 mm. The LED ring light is mounted with three screws on an adapter, which is screwed on to the zoom. Scope of delivery includes a power pack with infinitely variable dimming. In the event of an order as spare part or for other microscopes, price and order number are as follows:

**LED ring light for KITOZOOM series**
- **Order no. LED-R**

## LED-U



In the **KITO 20**, **KITO 30** and **KITO 40** models an LED bottom light plate is included in the system price. This diffuse LED bottom light is an ideal solution for all applications where a parallel bottom light is not required for precise measurement. The round illumination area has a diameter of 70 mm and the external diameter is 95 mm.

In the event of an order as spare part or for other microscopes, price and order number are as follows:

**LED bottom light for KITO 20, KITO 30 and KITO 40 series**
- **Order no. LED-U**

Injektor Solutions | Odengatan 40, 113 51 Stockholm | Telefon: +46 (0)8-7530004 | Fax: +46 (0)8-5000 13 99 | Mail: info@injektor.com | Web: www.injektor.com